Notes:

o/ A large Classic Golden Ratio based derivative of the Mar-Ken1opTT designed for Mark Audio Alpair 10p

If to be built as mirror imaged pairs – drivers are mounted off-centre (based on the golden ratio), Alternate driver placement optional. The driver brace moves with the driver and its placement with the driver magnet changing as the driver approaches centre-of-enclosure (horizontally).

2/ All panels 18mm

2/ All panels 18mm
3/ Vents are 18mm high, vent spacer is 31mm wide and centrally located
4/ brace shape is only suggestive – prime purpose is to brace driver (against more of
the enclosure material), it should to be about 35-40% holes – if you have to mount a
terminal cup i(recomended), you'll want to make sure the brace allows clearance).
Exact fit should be done with side off and driver "installed.
5/ Don't forget to angle cut the back of the driver cut-out to give it breathing room
6/ All internal panels lined with ~1/2" (12mm) cotton or wool felt (preferred), 3/4"
(19mm) poly-fluff batting, or 1" (25mm) fiberglass Note that it is hard to get into the
box after it is sealed up (means terminals need to be solderable from outside the box

7 do not overtighten driver screws. They should only be so tight as to stop a real (or imagined) washer from turning (finger tight).



Fat Classic GR Mar-Ken10p 0v92 sheet fcgr10p | Alpair 10p | 18mm plan © 2011-18 planet_10 enterprises limited 28- april-2018 | designed & drawn by dld for licensed use only

